

MI 3125 EurotestCOMBO



■ Handheld multifunctional installation tester

■ Easy to use



MI 3125 EurotestCOMBO is the appropriate instrument for the installation safety testing on TT and TN systems. The bright graphic display with backlight ensures that results, indications, measurement parameters and messages are clear, visible and easy to read. The red and green LEDs on either side of the display provide a clear PASS / FAIL evaluation of test results. EurotestCOMBO contains integrated characteristics of fuses and RCDs for the automatic evaluation of the line / loop impedance results. The handling of the instrument is designed to be as simple and clear as possible. Each test has its own individual help screen describing how to connect the instrument into the installation and how to perform a measurement. MI 3125 EurotestCOMBO performs continuity, insulation, RCD, loop, line, voltage, frequency and phase sequence tests required by the EN 61557 standard.

MEASURING FUNCTIONS:

- Insulation resistance with DC voltage.
- Continuity of PE conductors with 200 mA test current with polarity change.
- Line impedance.
- Loop impedance.
- Loop impedance with Trip Lock RCD function.
- TRMS voltage and frequency.
- Phase sequence.
- RCD testing (general and selective, type AC, A).

KEY FEATURES:

- **LED Pass/Fail indicators:** two LED indicators for PASS / FAIL evaluation of test results are placed on both sides of the LCD.
- **Help screens:** instrument comes complete with built-in help screens for referencing on site.
- **Built-in fuse tables:** this unique feature allows automatic evaluation of the line / loop impedance results compared to the regulations.
- **Online voltage monitoring:** monitors all 3 voltages in real-time.

- **Earth resistance measurement:** instrument performs 3-wire earth resistance testing with two additional rods.
- **Upgradeable:** if changes occur to the regulations, upgrades can be made to the firmware to keep the unit up to date.
- **Polarity swap:** automatic polarity reversal on continuity test.
- **Insulation range:** wide range of insulation test voltages from 50 V to 1000 V, reading up to 1000 MΩ.
- **Trip Lock function:** Zs (RCD) function performs a loop impedance test without tripping the RCD.
- **Multi-system testing:** tests on single and multiphase TT and TN systems.
- **Built-in charger & rechargeable batteries:** unit has a built-in charging circuit and comes complete with a set of rechargeable NiMH batteries.
- **RCD auto:** automated RCD testing procedure significantly reduces test time.

APPLICATIONS

- Initial and periodic testing of domestic and industrial installations.
- Testing of single and multiphase systems.
- Testing of TT and TN systems.

STANDARDS

- Functionality: IEC/EN 61557
- Other reference standards for testing: BS 7671; EN 61008; EN 61009; EN 60364-4-41; AS/NZ 3760
- Electromagnetic compatibility (EMC): EN 61326
- Safety (LVD): EN 61010-1; EN 61010-031

Technical specifications

Function	Measuring range	Resolution	Accuracy
Insulation resistance (EN 61557-2)	U = 50, 100, 250 V _{DC} :		
	R: 0.00 MΩ ... 19.99 MΩ	0.01 MΩ	±(5 % of reading + 3 digits)
	20.0 MΩ ... 99.9 MΩ	0.1 MΩ	±10 % of reading
	100.0 MΩ ... 199.9 MΩ	0.1 MΩ	±20 % of reading
	U = 500 V _{DC} , 1 kV _{DC} :		
	R: 0.00 MΩ ... 19.99 MΩ	0.01 MΩ	±(5 % of reading + 3 digits)
Continuity 200 mA of PE conductor with polarity change (EN 61557-4)	20.0 MΩ ... 99.9 MΩ	0.1 MΩ	±5 % of reading
	200 MΩ ... 999 MΩ	1 MΩ	±10 % of reading
	0.00 Ω ... 19.99 Ω	0.01 Ω	±(3 % of reading + 3 digits)
Loop impedance (EN 61557-3)	20.0 Ω ... 199.9 Ω	0.1 Ω	±5 % of reading
	200 Ω ... 1999 Ω	1 Ω	±5 % of reading
	0.00 Ω ... 9.99 Ω	0.01 Ω	±(5 % of reading + 5 digits)
	10.0 Ω ... 99.9 Ω	0.1 Ω	±(5 % of reading + 5 digits)
Line impedance (EN 61557-3)	100 Ω ... 999 Ω	1 Ω	±10 % of reading
	1.00 kΩ ... 9.99 kΩ	10 Ω	±10 % of reading
	0.00 Ω ... 9.99 Ω	0.01 Ω	±(5 % of reading + 5 digits)
	10.0 Ω ... 99.9 Ω	0.1 Ω	±(5 % of reading + 5 digits)
Voltage	100 Ω ... 999 Ω	1 Ω	±10 % of reading
	1.00 kΩ ... 9.99 kΩ	10 Ω	±10 % of reading
Frequency	0 V ... 550 V	1 V	±(2 % of reading + 2 digits)
	0.00 Hz ... 9.99 Hz	0.01 Hz	±(0.2 % of reading + 1 digits)
Phase sequence (EN 61557-7)	10.0 Hz ... 499.9 Hz	0.1 Hz	±(0.2 % of reading + 1 digits)
	1.2.3 or 3.2.1		
RCD testing (EN 61557-6)	I _{ΔN} : 10 mA, 30 mA, 100 mA, 300 mA, 500 mA, 1 A		
- Contact voltage U _c	0.0 V ... 19.9 V	0.1 V	(-0% / +15%) of reading ±10 d.
	20.0 V ... 99.9 V	0.1 V	(-0% / +15%) of reading
- Trip-out time	0 ms ... 40.0 ms	0.1 ms	±1 ms
	0 ms ... max. time	0.1 ms	±3 ms
- Trip-out current	0.2 x I _{ΔN} ... 1.1 x I _{ΔN} (AC type)	0.05 x I _{ΔN}	±0.1 x I _{ΔN}
	0.2 x I _{ΔN} ... 2.2 x I _{ΔN} (A type, I _{ΔN} < 30 mA)	0.05 x I _{ΔN}	±0.1 x I _{ΔN}
	0.2 x I _{ΔN} ... 1.5 x I _{ΔN} (A type, I _{ΔN} ≥ 30 mA)	0.05 x I _{ΔN}	±0.1 x I _{ΔN}
Earth resistance (EN 61557-5)	0.00 Ω ... 19.99 Ω	0.01 Ω	±(5 % of reading + 5 digits)
	20.0 Ω ... 199.9 Ω	0.1 Ω	±(5 % of reading + 5 digits)
	200 Ω ... 9999 Ω	1 Ω	±(5 % of reading + 5 digits)

General

Power supply	6 x 1.5 V alkaline or 6 x 1.2 V rechargeable batteries, size AA
Overvoltage category	600 V / CAT III; 300 V / CAT IV
Protection class	double insulation
COM port	RS232 and USB
Dimensions	140 x 80 x 230 mm
Weight	1.0 kg

Ordering Information: Standard Set MI3125



- Instrument MI3125 InstalTestCOMBO
- Set of carrying straps
- Test probe, 3pcs (black, red, green)
- Crocodile clip, 3pcs (black, red, green)
- Test lead, 3 x 1.5m (black, red, green)
- Mains measuring cable, 1.5m
- 6 NiMH, type AA + Power supply adapter
- Short instruction manual + online download
- Calibration certificate

Optional accessories:

Photo	Order No.	Description
	A 1110	Three phase adapter
	A 1111	Three phase adapter with switch
	A 1160	Fast charger with a set of 6 pcs NiMH batteries AA
	A 1198	Magnetic contact probe
	A 1153	Test lead, black, 20 m
	A 1154	Test lead, black, 4 m
	A 1168	Plug commander
	A 1401 BLK	Tip commander
	A 1303	Soft hand strap
	A 1289	Soft carrying bag
	A 1271	Small soft carrying bag
	S 2026	Earth 20 m set, 3 wire
	S 2027	Earth 50 m set, 3 wire



Measuring and Regulation Equipment Manufacturer

METREL d.d.
Ljubljanska 77
SI-1354 Horjul
Tel: + 386 (0)1 75 58 200
Fax: + 386 (0)1 75 49 226
E-mail: metrel@metrel.si
http://www.metrel.si

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.